

HOFMANN®



EEWA712AL

***geoliner*® 600/650**

WHEEL ALIGNERS

geoliner® 600/650



FEATURES

VERSATILE, ACCURATE HARDWARE

- Digital cameras produce accurate, live alignment readings and diagnostic data
- Passive front and rear targets improve durability with no electronics to damage

VEHICLE ORIENTATION DIRECTIONAL INDICATOR* (VODI™)

- Guides the technician through the measuring process
- Reduces the amount of time spent walking back and forth from the vehicle to the aligner

OPTIONAL ACCESSORIES

- AC200 wheel clamp extension kit: EAK0268J62A
- AC200 Alloy quick clamp kit: EAK0268J63A
- AC200 Wheel clamp floor stand: EAK0269J71A
- Fixed-height camera support: EAA0321J01A
- Variable-height camera support: EAA0321J19A
- Electronic tilt camera support kit: EAK0289J79A

STANDARD ACCESSORIES

- AC200 wheel clamps and targets
- Steering wheel holder
- Brake pedal depressor
- Color Inkjet Printer

SPECIFICATIONS

- Wheel size: 13" - 24" (33cm - 61cm)
- Tire diameter: Unlimited
- Track width: 48" - 96" (122cm - 244cm)
- Wheel base: 79" - 180" (201cm - 457cm)
- Power requirements: 120/230V 1Ph 50/60Hz

*Patented and/or Patent-Pending Features

†EEWA712AL Only

ADDITIONAL KEY FEATURES

- Optional Fixed, Variable-Height†, Tilt Camera Support
- AC200 Wheel Clamps
- Vehicle Orientation Directional Indicator* (VODI™)
- EZ-LINK™ Steering Angle Sensor (SAS) Reset Information
- Live Readings
- Comprehensive Alignment Specification Database
- EZ-TOE*
- Two and Four Wheel Alignment Capability
- Help Videos



EEWA712AL
geoliner 650
Cabinet Configuration



EEWA721AL
geoliner 600
Shelf Mount Configuration



USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com



Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca

